

LED COMBO EXIT SIGN WITH EMERGENCY LIGHT · 120/277 V

Combo emergency exit light

Universal field-selectable single- or double-face exit sign with emergency lighting, in red or green letters.

90 min	24 h	120/277 V	6 in
BATTERY DISCHARGE TIME	CHARGING TIME	INPUT VOLTAGE	ILLUMINATED CHARACTERS

PROJECT _____ TYPE _____ CATALOG NO. _____ DATE _____

UL 924 · DAMP LOCATION

Specification and features

Combo exit sign and emergency light, in red or green letters.

ILLUMINATION	Long-life, high-intensity LEDs
HOUSING	Injection-molded thermoplastic ABS housing
INPUT VOLTAGE	120/277VAC 60Hz
BATTERY	Maintenance-free 4.8V NiCad battery
CHARGING TIME	24 hours
FINISH	White
CERTIFICATIONS	UL 924 listed for damp locations.

LAMPS	30 pcs 0.1W SMD LED, total 3W
LEGEND	Fully illuminated 6" characters
INPUT RATING	5.0W, 50mA
OPERATING TEMPERATURE	0°C to 40°C (32°F to 104°F)
DISCHARGE TIME	90 minutes
DIMENSIONS	320 × 218 × 47 mm

Models

ORDER INFORMATION

MODEL	VOLTAGE	COLOR OF LETTER	DISCHARGE TIME	CERTIFICATE
A-EC5-UNV-AR	120/277V	Red	90 minutes	UL
A-EC5-UNV-AG	120/277V	Green	90 minutes	UL

Features

- Universal field-selectable single-/double-face
- Wall, end and ceiling mounting
- Suitable for damp locations
- UL 924 listed

Ordering and dimensions

Catalog number breakdown

LEFT TO RIGHT

A-EC5-UNV – AR

1	2

1	Series	A-EC5-UNV	A- = Allmax · EC = exit sign with emergency light · 5 = 5.0 W · UNV = 120–277 V (combo emergency exit light, 120/277 V, 90 minutes, UL)
2	Letter color	AR · AG	AR = red letters · AG = green letters

EXAMPLE A-EC5-UNV-AR (red letters) · A-EC5-UNV-AG (green letters)

Dimensions

Unit: mm. Dimensioned drawing.

FRONT AND SIDE VIEW

