

5W-PENDANT · EXPLOSION PROOF

Explosion-Proof Exit Sign — Pendant Mount

Explosion-Proof Exit Sign — Pendant Mount.

600 lm	AC 100–277 V, 50/60 Hz	5 W wall / pendant mount	90+ minutes (1.5 hours)
MAXIMUM OUTPUT (5 W WALL / PENDANT MOUNT)	INPUT VOLTAGE	MAXIMUM-WATTAGE MODEL	EMERGENCY BATTERY BACKUP

PROJECT _____ TYPE _____ CATALOG NO. _____ DATE _____

Specification

Values below apply only where stated. Blank source fields are shown as “Not stated”; no value is inferred.

POWER FACTOR	0.97	EMERGENCY BATTERY BACKUP	90+ minutes (1.5 hours)
HOUSING MATERIAL	Die-cast aluminum (ADC12)	CONDUIT ENTRY	M25 × 1.5 or NPT 3/4"-14
OPERATING TEMPERATURE	-40°C to +45°C / +50°C / +55°C (model dependent)	MOUNTING OPTIONS	Wall mount / pendant ceiling mount

Model data

Maximum-wattage cover values are taken from 5 W wall / pendant mount.

Variant	Wattage	Luminous flux	CCT	CRI	Input voltage	Dimensions
5 W wall / pendant mount	5 W	600 lm	Not stated	Not stated	AC 100–277 V, 50/60 Hz	Not stated

Product page: https://allmaxlighting.com/products/explosion-proof-exit-sign-pendant/ · Source record: Allmax Catalog 2026 (redesigned), page 53.