

5W-WALL · EXPLOSION PROOF

Explosion-Proof LED Exit Sign — Wall Mount

Explosion-Proof LED Exit Sign — Wall Mount.

600 lm MAXIMUM OUTPUT (5 W WALL MOUNT)	AC 100–277 V, 50/60 Hz INPUT VOLTAGE	5 W wall mount MAXIMUM-WATTAGE MODEL	90+ minutes (1.5 hours), self-contained battery EMERGENCY BATTERY BACKUP

PROJECT _____ TYPE _____ CATALOG NO. _____ DATE _____

Specification

Values below apply only where stated. Blank source fields are shown as “Not stated”; no value is inferred.

POWER FACTOR	0.97	EMERGENCY BATTERY BACKUP	90+ minutes (1.5 hours), self-contained battery
LIFESPAN	> 50,000 hours	HOUSING MATERIAL	ADC12 aluminum alloy with anti-corrosion powder coating
CONDUIT ENTRY	M25 × 1.5 or NPT 3/4"-14	OPERATING TEMPERATURE	-40°C to +45°C / +50°C / +55°C (model dependent)
MOUNTING OPTIONS	Wall mount		

Model data

Maximum-wattage cover values are taken from 5 W wall mount.

Variant	Wattage	Luminous flux	CCT	CRI	Input voltage	Dimensions
5 W wall mount	5 W	600 lm	Not stated	Not stated	AC 100–277 V, 50/60 Hz	Not stated

Product page: https://allmaxlighting.com/products/explosion-proof-exit-sign-wall/ · Source record: Allmax Catalog 2026 (redesigned), page 52.